

WEST

[Help](#)[Logout](#)[Interrupt](#)[Main Menu](#)[Search Form](#)[Posting Counts](#)[Show S Numbers](#)[Edit S Numbers](#)[Preferences](#)[Cases](#)

Search Results -

Terms	Documents
L1 and (PVC or polyvinyl chloride)	19

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L3

[Refine Search](#)[Recall Text](#)[Clear](#)

Search History

DATE: Tuesday, September 02, 2003 [Printable Copy](#) [Create Case](#)Set Name Query

side by side

Hit Count Set Name

result set

DB=DWPI; PLUR=YES; OP=ADJ

<u>L3</u>	L1 and (PVC or polyvinyl chloride)	19	<u>L3</u>
<u>L2</u>	L1 and (crystallizable)	0	<u>L2</u>
<u>L1</u>	\$2polyester and extru\$4 and (metal with (surface or substrate))	197	<u>L1</u>

END OF SEARCH HISTORY

WEST[Help](#)[Logout](#)[Interrupt](#)

Main Menu	Search Form	Posting Counts	Show S Numbers	Edit S Numbers	Preferences	Cases
---------------------------	-----------------------------	--------------------------------	--------------------------------	--------------------------------	-----------------------------	-----------------------

Search Results -

Terms	Documents
L1 and (metal with (surface or substrate or layer))	21

Database:

US Patents Full-Text Database	▲
US Pre-Grant Publication Full-Text Database	
JPO Abstracts Database	
EPO Abstracts Database	
Derwent World Patents Index	▼
IBM Technical Disclosure Bulletins	

Search:

L2

[Refine Search](#)[Recall Text](#)[Clear](#)**Search History**
DATE: Tuesday, September 02, 2003 [Printable Copy](#) [Create Case](#)
Set Name Query

side by side

DB=DWPI; PLUR=YES; OP=ADJ

<u>L2</u>	L1 and (metal with (surface or substrate or layer))
<u>L1</u>	\$2polyester and (blend\$3 or mix\$4) and crystalli\$5 and (non\$1crystalli\$5 or amorphous)

Hit Count Set Name

result set

21 L2353 L1

END OF SEARCH HISTORY

WEST

☐

L3: Entry 7 of 19

File: DWPI

Jan 10, 1992

DERWENT-ACC-NO: 1992-061522

DERWENT-WEEK: 199208

COPYRIGHT 2003 DERWENT INFORMATION LTD

TITLE: Resin-coated metallic prod. - comprises metal substrate melt laminated with thermoplastic adhesive resin and PVC resin

PRIORITY-DATA: 1990JP-0111031 (April 25, 1990)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
JP 04007142 A	January 10, 1992		000	

INT-CL (IPC): B32B 15/08

ABSTRACTED-PUB-NO: JP 04007142A

BASIC-ABSTRACT:

The surface of a metal prod. is melt laminated with a thermoplastic adhesive resin having a melt index = 0.01-5 as measured at 180 deg C and a load = 2.16 kg and polyvinyl chloride resin having a polymerisation deg. = 400-1300.

The metal substrate is e.g., Al, steel, Cu, etc. and pretreated by degreasing, pickling or blasting to remove impurities and fouling. The polyvinyl chloride resin is e.g. polyvinyl chloride homopolymer, vinyl chloride/vinyl acetate copolymer, ethylene/vinyl chloride/vinyl acetate terpolymer, ethylene/vinyl acetate copolymer, etc. having the specified deg. of polymerisation for providing high mouldability, mechanical and chemical properties and blended opt. with a stabiliser, working aid, lubricant, impact resistance improver, etc. The adhesive resin is pref. satd. crystalline polyester resin, polyamide resin or resin of hot melt type blended with an inorganic filler or a crosslinked partly to provide a high mol. wt. or blended with a resin having a high melt viscosity to control the melt index = 0.01-5. The lamination of adhesive resin and polyvinyl chloride resin are coated on the metal substrate by the co-extrusion.

ADVANTAGE - The adhesive layer and the polyvinyl chloride resin layer are melt laminated uniformly and firmly with the metal substrate.